

# GETEC

## HYDRAMAX HMCC-C520

### *Hydraulically driven* **AC GENERATOR**

**Voltage**

120 V or  
120/240 V

**AC POWER**

5200 Watt

**VOLTAGE REGUL.**

3%

**FREQUENCY**

60 HZ

**INULATION C+H**

50 HZ Models  
available



<b>Overall Efficiency</b>	<b>81 %</b>
<b>Operating Speed</b>	<b>3600 RPM</b>
<b>Minimum Flow</b>	<b>7.5 GPM</b>
<b>Ideal Flow</b>	<b>10 GPM</b>
<b>Maximum Flow</b>	<b>15 GPM</b>
<b>Free Air Flow</b>	<b>8 cfm</b>
<b>Recommended Filtration</b>	<b>10 m</b>
<b>Max.Oil Temperature</b>	<b>180 F</b>
<b>Recommended Tank Size</b>	<b>20 Gal.</b>

### **Features and Specifications**

- Completely Brushless, Maintenance free.
- Pure Sinewave Output.
- Environmentally safe , no Pollution
- Can mount in any Position.
- Hydr.Motor includes Pressure compensating Flow Control. ( Build in )
- Will operate on Open and Closed Systems
- All this in a Package of 8" high , 8.5" wide and 17" long and weights only 79 Lbs
- The Hydraulic Requirement is 7.5 GPM @ 1450 PSI ( other Flow requirements are available )

# GETEC INC

624 Harris Road  
Ferndale New York 12734

(845)-292-0800

<http://www.getec.com>

email SALES@GETEC.COM